

SAFETY DATA SHEET



Date Issued : 05/15/2008
 SDS No : TC-318 PART A
 Date Revised : 10/10/2018
 Revision No : 2

TC-318 PART A

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: TC-318 PART A

GENERAL USE: Polyurethane resin

MANUFACTURER

BJB Enterprises, Inc.
 14791 Franklin Avenue
 Tustin, CA 92780
Emergency Phone: (714) 734-8450

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (USA & Canada): (800) 424-9300
 or (703) 527-3887 CCN# 2820

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS**Health:**

Acute Toxicity (Inhalation), Category 4
 Skin Irritation, Category 2
 Eye Irritation, Category 2A
 Respiratory Sensitization, Category 1
 Skin Sensitization, Category 1
 Carcinogenicity, Category 2
 Reproductive Toxicity, Category 1
 Target Organ Toxicity (Single exposure), Category 3
 Target Organ Toxicity (Repeated exposure), Category 2

Environmental:

Chronic Hazards to the Aquatic Environment, Category 3

GHS LABEL

Health hazard



Exclamation
 mark

SIGNAL WORD: DANGER

HAZARD STATEMENTS

H332: Harmful if inhaled.
 H315: Causes skin irritation.
 H319: Causes serious eye irritation.
 H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H317: May cause an allergic skin reaction.
 H351: Suspected of causing cancer.
 H360: May damage fertility or the unborn child.
 H335: May cause respiratory irritation.
 H373: May cause damage to organs through prolonged or repeated exposure.
 H412: Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS**Prevention:**

TC-318 PART A

- P201: Obtain special instructions before use.
 P202: Do not handle until all safety precautions have been read and understood.
 P260: Do not breathe dust/fume/gas/mist/vapours/spray.
 P271: Use only outdoors or in a well-ventilated area.
 P284: In case of inadequate ventilation wear respiratory protection.
 P264: Wash thoroughly after handling.
 P272: Contaminated work clothing should not be allowed out of the workplace.
 P280: Wear protective gloves/protective clothing/eye protection/face protection.
 P273: Avoid release to the environment.

Response:

- P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P342+P311: If experiencing respiratory symptoms: Call a POISON CENTER/doctor/physician.
 P302+P352: IF ON SKIN: Wash with plenty of soap and water.
 P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
 P362+P364: Take off contaminated clothing and wash it before reuse.
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337+P313: If eye irritation persists: Get medical advice/attention.
 P308+P313: IF exposed or concerned: Get medical advice/ attention.

Storage:

- P403+P233: Store in a well-ventilated place. Keep container tightly closed.
 P405: Store locked up.

Disposal:

- P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Chemical Name | Wt.% | CAS |
|--|---------|------------|
| 4,4'-Diphenylmethane diisocyanate | 30 - 60 | 101-68-8 |
| Benzene, 1,1'-methylenebis[4-isocyanato-, homopolymer | 10 - 30 | 25686-28-6 |
| 1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich | 10 - 30 | 68515-49-1 |
| Tris(2-chloroethyl)phosphate | 1 - 5 | 115-96-8 |
| 2,6-di-tert-butyl-p-cresol | 0.1 - 1 | 128-37-0 |
| Naphthalene | < 0.001 | 91-20-3 |

4. FIRST AID MEASURES

- EYES:** Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get immediate medical attention.
- SKIN:** Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if irritation or rash develops. Wash clothing before reuse.
- INGESTION:** If swallowed, call a physician immediately. Do not induce vomiting unless directed to do so by medical personnel. Provided the patient is conscious, wash out mouth with water. Never give anything by mouth to an unconscious person.
- INHALATION:** Remove to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get immediate medical attention.
- NOTES TO PHYSICIAN:** Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

5. FIRE FIGHTING MEASURES

- EXTINGUISHING MEDIA:** Water spray, carbon dioxide, dry chemical, or foam.
- HAZARDOUS COMBUSTION PRODUCTS:** Carbon monoxide, carbon dioxide, nitrogen oxides, hydrocarbons, hydrogen cyanide, hydrogen chloride gas, and phosphorus oxides.

TC-318 PART A

FIRE FIGHTING PROCEDURES: Cool fire exposed containers with water spray. Remove containers from the fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

FIRE FIGHTING EQUIPMENT: Firefighters should wear positive pressure self-contained breathing apparatus (SCBA) and consider use of unmanned hose holders or monitor nozzles for fighting large fires.

6. ACCIDENTAL RELEASE MEASURES

SPILL AND LEAK PROCEDURES: Evacuate unnecessary personnel from the spill area. Eliminate all sources of ignition. Ensure adequate ventilation. Use personal protective equipment. Dike and contain spill. Prevent product from entering drains or waterways. Absorb with non-combustible material (such as sand, earth, diatomaceous earth, or vermiculite) and transfer to a container for disposal according to local/national regulations.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Do not discharge into drains, surface waters, or groundwater.

GENERAL PROCEDURES: Refer to section 8 of SDS for personal protection details.

RELEASE NOTES: Composition and extent of any spill should be evaluated against local regulations and reported to the proper agencies, if necessary.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Avoid breathing vapor over open containers. Avoid open container exposure to damp air. Avoid breathing aerosols, mists, and vapors.

HANDLING: Use appropriate personal protective equipment as specified in Section 8. Handle in a well-ventilated area. Handle and use in a manner consistent with good industrial/manufacturing techniques and practices.

STORAGE: Store in a dry and well-ventilated place, away from excessive heat, in original or similar container. Avoid unnecessary contact. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials.

STORAGE TEMPERATURE: 65-80°F (18-27°C)

SHELF LIFE: 6 months from date of shipment under manufacturers recommended storage conditions.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**EXPOSURE GUIDELINES**

| OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200) | | | | |
|---|---|----------|---------------------|--------------------|
| Chemical Name | EXPOSURE LIMITS | | ppm | mg/m ³ |
| | Type | | | |
| 4,4'-Diphenylmethane diisocyanate | OSHA PEL | TWA | - | - |
| | | STEL | - | - |
| | | C | 0.02 | 0.2 |
| | ACGIH TLV | TWA | 0.005 | - |
| | | STEL | - | - |
| | NIOSH REL | TWA | 0.005 | 0.05 |
| | | STEL | - | - |
| | | C | 0.02 ^[1] | 0.2 ^[1] |
| | Benzene, 1,1'-methylenebis[4-isocyanato-, homopolymer | OSHA PEL | TWA | - |
| STEL | | | - | - |
| ACGIH TLV | | TWA | - | - |
| | | STEL | - | - |
| NIOSH REL | | TWA | - | - |
| | | STEL | - | - |

TC-318 PART A

| | | | | |
|--|-------------|----------|-----|----|
| 1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich | OSHA PEL | TWA | - | - |
| | | STEL | - | - |
| | ACGIH TLV | TWA | - | - |
| | | STEL | - | - |
| | NIOSH REL | TWA | - | - |
| | | STEL | - | - |
| Tris(2-chloroethyl)phosphate | OSHA PEL | TWA | - | - |
| | | STEL | - | - |
| | ACGIH TLV | TWA | - | - |
| | | STEL | - | - |
| | NIOSH REL | TWA | - | - |
| | | STEL | - | - |
| 2,6-di-tert-butyl-p-cresol | OSHA PEL | TWA | - | - |
| | | STEL | - | - |
| | ACGIH TLV | TWA | - | - |
| | | STEL | - | - |
| | NIOSH REL | TWA | - | 10 |
| | Naphthalene | OSHA PEL | TWA | 10 |
| STEL | | | - | - |
| ACGIH TLV | | TWA | 10 | 52 |
| | | STEL | 15 | 79 |
| NIOSH REL | | TWA | 10 | 50 |
| | | STEL | 15 | 75 |
| Footnotes: | | | | |
| 1. 10-minute | | | | |

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Safety goggles or glasses are recommended. Plastic face shields should be used for complete face protection to protect against possible splashing or spraying of material. ANSI Z87.1 or approved equivalent.

SKIN: Chemical-resistant gloves and chemical goggles, face-shield, and synthetic apron or coveralls should be used to prevent contact with eyes, skin, or clothing. Wear nitrile or neoprene gloves. Chemical resistant gloves lined with polyethylene offer maximum protection.

RESPIRATORY: Exhaust ventilation recommended. An organic vapor cartridge or fresh air supplied respirator (NIOSH approved) may be necessary for certain applications. Consider the type of application, environmental concentrations, and other materials being used concurrently when determining respirator use and selection. Observe OSHA regulations for respirator use (29 CFR 1910.134).

PROTECTIVE CLOTHING: Protective clothing should be selected and used in accordance with 'Guidelines for the Selection of Chemical Protective Clothing' published by ACGIH.

WORK HYGIENIC PRACTICES: Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Wash hands before eating.

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Training is important. Follow all label precautions.

9. PHYSICAL AND CHEMICAL PROPERTIES

TC-318 PART A**PHYSICAL STATE:** Liquid**ODOR:** Slightly musty**COLOR:** Pale yellow**pH:** No data available**PERCENT VOLATILE:** 0.03**FLASH POINT AND METHOD:** 107.2°C (225°F) Pensky-Martens CC**VAPOR PRESSURE:** No data available**VAPOR DENSITY:** No data available**BOILING POINT:** No data available**SOLUBILITY IN WATER:** Reacts with water**SPECIFIC GRAVITY:** 1.15 (water=1) at 25°C (77°F)**VISCOSITY #1:** 60 Centipoise at 25°C (77°F)**(VOC):** < 0.4 g/l Calculated. Theoretical VOC minus water and exempt solvents.**10. STABILITY AND REACTIVITY****REACTIVITY:** Hazardous reactions will not occur under normal transport or storage conditions.**STABILITY:** This product is stable under normal ambient conditions of temperature and pressure.**CONDITIONS TO AVOID:** High temperatures, moisture, and freezing conditions.**POSSIBILITY OF HAZARDOUS REACTIONS:** Reaction with water produces carbon dioxide. Exothermic reaction with materials containing active hydrogen groups. The reaction becomes progressively more vigorous and can be violent at higher temperatures if the miscibility of the reaction partners is good or is supported by stirring or by the presence of solvents. MDI is insoluble with, and heavier than water and sinks to the bottom but reacts slowly at the interface. A solid water-insoluble layer of polyurea is formed at the interface by liberating carbon dioxide gas.**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide, carbon dioxide, nitrogen oxides, hydrocarbons, hydrogen cyanide, hydrogen chloride gas, and phosphorus oxides.**INCOMPATIBLE MATERIALS:** Water, strong bases, strong acids, strong oxidizing agents, and amines.**11. TOXICOLOGICAL INFORMATION****ACUTE TOXICITY**

| Chemical Name | ORAL LD ₅₀ | DERMAL LD ₅₀ | INHALATION LC ₅₀ |
|--|-----------------------|-------------------------|---------------------------------|
| 4,4'-Diphenylmethane diisocyanate | > 10000 mg/kg Rat | > 9400 mg/kg Rabbit | 490 mg/m ³ Rat (4 h) |
| Benzene, 1,1'-methylenebis[4-isocyanato-, homopolymer | > 5000 mg/kg Rat | No data available | 0.49 mg/l Rat |
| 1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich | > 10 g/kg Rat | > 3.16 g/kg Rabbit | > 0.13 mg/l Rat |
| Tris(2-chloroethyl)phosphate | 1150 mg/kg Rat | > 5000 mg/kg Rabbit | > 5 mg/l Rat (4 h) |
| 2,6-di-tert-butyl-p-cresol | No data available | No data available | No data available |
| Naphthalene | 490 mg/kg Rat | 20000 mg/kg Rabbit | > 0.4 mg/l Rat (4 h) |

SKIN CORROSION/IRRITATION: Causes skin irritation.**SERIOUS EYE DAMAGE/IRRITATION:** Causes serious eye irritation.**RESPIRATORY OR SKIN SENSITISATION:** May cause sensitization by inhalation and skin contact.**GERM CELL MUTAGENICITY:** No data available**CARCINOGENICITY**

TC-318 PART A

| Chemical Name | NTP Status | IARC Status |
|-----------------------------------|------------|-------------|
| 4,4'-Diphenylmethane diisocyanate | | 3 |
| Tris(2-chloroethyl)phosphate | | 3 |
| 2,6-di-tert-butyl-p-cresol | | 3 |
| Naphthalene | 2 | 2B |

REPRODUCTIVE TOXICITY: May damage fertility or the unborn child.

STOT-SINGLE EXPOSURE: May cause respiratory irritation.

STOT-REPEATED EXPOSURE: May cause damage to organs through prolonged or repeated exposure.

ASPIRATION HAZARD: No data available

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: This product may cause risk of hazardous effects to the environment.

ECOTOXICOLOGICAL INFORMATION: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Avoid release to the environment.

BIOACCUMULATION/ACCUMULATION: No data available

DISTRIBUTION: No data available

CHEMICAL FATE INFORMATION: No data available

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protections and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION): Not Regulated

AIR (ICAO/IATA): Not Regulated

VESSEL (IMO/IMDG): Not Regulated

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Acute Health Hazard, Chronic Health Hazard

313 REPORTABLE INGREDIENTS: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

EPCRA SECTION 313 SUPPLIER NOTIFICATION

| Chemical Name | Wt. % | CAS | Comments |
|-----------------------------------|---------|----------|---|
| 4,4'-Diphenylmethane diisocyanate | 30 - 60 | 101-68-8 | Diisocyanate Compounds (Category Code N120) |

CERCLA (COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA REGULATORY: This product contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

| Chemical Name | Wt. % | CERCLA RQ |
|-----------------------------------|---------|------------|
| 4,4'-Diphenylmethane diisocyanate | 30 - 60 | 5,000 lbs. |
| Naphthalene | < 0.001 | 100 lbs. |


TC-318 PART A**TSCA (TOXIC SUBSTANCE CONTROL ACT)**

TSCA REGULATORY: This product does not contain any substances subject to TSCA Section 12(b) export notification.

TSCA STATUS: This product or its components are listed in or exempt from the TSCA inventory requirements.

OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)

29 CFR1910.119--PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS CHEMICALS: None of the chemicals in this product are considered highly hazardous by OSHA.

CALIFORNIA PROPOSITION 65:  **WARNING:** This product can expose you to chemicals including [see table below], which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

| Chemical Name | Wt. % | Listed |
|--|---------|------------------------|
| 1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich | 10 - 30 | Developmental Toxicity |
| Tris(2-chloroethyl)phosphate | 1 - 5 | Cancer |
| Naphthalene | < 0.001 | Cancer |

OSHA HAZARD COMM. RULE: The contents of the SDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

CANADA

WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM): This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

DOMESTIC SUBSTANCE LIST (INVENTORY): All components in this product are listed in or exempted from the Domestic Substances List (DSL) or the Non-Domestic Substances List (NDSL).

GENERAL COMMENTS:

DIDP RESTRICTIONS: This product contains diisodecyl phthalate (DIDP), CAS# 68515-49-1 EINECS# 271-091-4. In the U.S., there is an interim prohibition on DIDP above 0.1 percent by weight (one thousand parts per million) in toys intended for children age 12 and under that can be placed in a child's mouth and child care articles for children age 3 and under [H.R. 4040, The Consumer Safety Improvement Act of 2008]. In the EU, DIDP shall not be used as substance or as constituents of preparations, at concentrations of greater than 0.1 percent by weight (one thousand parts per million) of the plasticized material, in toys and child care articles which can be place in the mouth by children. Such toys and child care articles containing DIDP in concentrations greater than the limit mentioned above shall not be placed on the market [Directive 2005/84/EC].

16. OTHER INFORMATION


REASON FOR ISSUE: Revision

Date Revised: 10/10/2018

REVISION SUMMARY: This SDS replaces the 10/14/2015 SDS.

HMIS RATING

| | | |
|----------------------------|---|----------|
| HEALTH | * | 2 |
| FLAMMABILITY | | 1 |
| PHYSICAL HAZARD | | 0 |
| PERSONAL PROTECTION | | X |

NFPA CODES

HMIS RATINGS NOTES: Personal Protection: See Section 8

MANUFACTURER DISCLAIMER: This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of BJB Enterprises, Inc. The data on this sheet relates only to the specific material designated herein. BJB Enterprises, Inc. assumes no legal responsibility for use or reliance upon this data.