

SAFETY DATA SHEET



Date Prepared : 06/05/2013
 SDS No : 6835 GRAY
 Date Revised : 06/17/2016
 Revision No : 1

6835 GRAY

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 6835 GRAY
GENERAL USE: Pigment
CHEMICAL FAMILY: Non-aqueous colorant

MANUFACTURER

BJB Enterprises, Inc.
 14791 Franklin Avenue
 Tustin, CA 92780
Emergency Phone: (714) 734-8450

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (USA & Canada): (800) 424-9300
 or (703) 527-3887 CCN# 2820

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

This product does not meet the criteria for classification.

GHS LABEL

Not Applicable

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Titanium oxide (TiO ₂)	30 - 60	13463-67-7
1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich	15 - 40	68515-49-1
Carbon black	5 - 10	1333-86-4
Aluminum Hydroxide	1 - 5	21645-51-2
Silica, Amorphous	1 - 5	7631-86-9

4. FIRST AID MEASURES

EYES: Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops.

SKIN: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if irritation or rash develops. Wash clothing before reuse.

INGESTION: If swallowed, call a physician immediately. Do not induce vomiting unless directed to do so by medical personnel. Provided the patient is conscious, wash out mouth with water. Never give anything by mouth to an unconscious person.

INHALATION: Remove to fresh air. Seek medical attention if breathing becomes difficult or if respiratory irritation develops.

NOTES TO PHYSICIAN: Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Water spray, carbon dioxide, dry chemical, or foam.

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide and carbon dioxide.

6835 GRAY

FIRE FIGHTING PROCEDURES: Cool fire exposed containers with water spray. Remove containers from the fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

FIRE FIGHTING EQUIPMENT: Firefighters should wear positive pressure self-contained breathing apparatus (SCBA) and consider use of unmanned hose holders or monitor nozzles for fighting large fires.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Eliminate sources of ignition. Evacuate the area. Clean-up should only be performed by trained personnel. People dealing with a major spill should wear full protective clothing including appropriate respiratory protection. Prevent product spill from entering sewers or waterways. Neutralize small spills with a decontaminant.

LARGE SPILL: Contain and absorb large spills onto an inert, non-flammable adsorbent carrier (such as earth or sand). Do not use combustible materials such as saw dust. Use only spark resistant and explosion proof recovery devices. Shovel into open-top drums or plastic bags for further decontamination, if necessary. Wash the spill area clean with a liquid decontaminant. Remove and properly dispose of residues. Notify applicable government authorities if release is reportable. (See CERCLA in Section 15).

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Do not discharge into drains or rivers.

GENERAL PROCEDURES: Refer to section 8 of SDS for personal protection details.

RELEASE NOTES: Composition and extent of any spill should be evaluated against local regulations and reported to the proper agencies, if necessary.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Keep away from sources of ignition. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Avoid breathing vapor over open containers. Avoid open container exposure to damp air. Avoid breathing aerosols, mists, and vapors.

HANDLING: Use appropriate personal protective equipment as specified in Section 8. Handle in a well-ventilated area. Handle and use in a manner consistent with good industrial/manufacturing techniques and practices.

STORAGE: Store in a dry and well-ventilated place, away from excessive heat in the original or similar container. Avoid sources of ignition and incompatible materials. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials. Avoid unnecessary contact.

STORAGE TEMPERATURE: 65-80°F (18-27°C)

SHELF LIFE: 24 months from date of shipment under manufacturers recommended storage conditions.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

6835 GRAY

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
Chemical Name	EXPOSURE LIMITS			
	Type		ppm	mg/m ³
Titanium oxide (TiO ₂)	OSHA PEL	TWA	NE	15 Total Dust
		STEL	NE	NE
	ACGIH TLV	TWA	NE	10
		STEL	NE	NE
	Supplier OEL	TWA	NE	NE
		STEL	NE	NE
1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich	OSHA PEL	TWA	NE	NE
		STEL	NE	NE
	ACGIH TLV	TWA	NE	NE
		STEL	NE	NE
	Supplier OEL	TWA	NE	5
		STEL	NE	NE
Carbon black	OSHA PEL	TWA	NE	3.5
		STEL	NE	NE
	ACGIH TLV	TWA	NE	3.5
		STEL	NE	NE
	Supplier OEL	TWA	NE ^[1]	3.5 ^[1]
		STEL	NE	NE
Aluminum Hydroxide	OSHA PEL	TWA	NE	NE
		STEL	NE	NE
	ACGIH TLV	TWA	NE	10
		STEL	NE	NE
	Supplier OEL	TWA	NE	NE
		STEL	NE	NE
Silica, Amorphous	OSHA PEL	TWA	20 mppcf ^[2]	80 %SiO ₂ ^[2]
		STEL	NE	NE
	ACGIH TLV	TWA	NE	10 Total Dust
		STEL	NE	NE
	Supplier OEL	TWA	NE ^[1]	6 ^[1]
		STEL	NE	NE

Footnotes:

1. NIOSH REL
2. Mineral Dusts

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels

6835 GRAY

below recommended exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Safety goggles or glasses are recommended. Plastic face shields should be used for complete face protection to protect against possible splashing or spraying of material. ANSI Z87.1 or approved equivalent.

SKIN: Chemical-resistant gloves and chemical goggles, face-shield, and synthetic apron or coveralls should be used to prevent contact with eyes, skin, or clothing. Wear nitrile or neoprene gloves. Chemical resistant gloves lined with polyethylene offer maximum protection.

RESPIRATORY: Exhaust ventilation recommended. An organic vapor cartridge or fresh air supplied respirator (NIOSH approved) may be necessary for certain applications. Consider the type of application, environmental concentrations, and other materials being used concurrently when determining respirator use and selection. Observe OSHA regulations for respirator use (29 CFR 1910.134).

PROTECTIVE CLOTHING: Protective clothing should be selected and used in accordance with 'Guidelines for the Selection of Chemical Protective Clothing' published by ACGIH.

WORK HYGIENIC PRACTICES: Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Wash hands before eating.

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Training is important. Follow all label precautions.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Slight

COLOR: Gray

PERCENT VOLATILE: Nil

FLASH POINT AND METHOD: 107.2°C (225°F)

VAPOR PRESSURE: Not Established

VAPOR DENSITY: Not Established

BOILING POINT: Not Established

SOLUBILITY IN WATER: Negligible

SPECIFIC GRAVITY: 1.79 (water=1) at 25°C (77°F)

(VOC): Nil

10. STABILITY AND REACTIVITY

REACTIVITY: Hazardous reactions will not occur under normal transport or storage conditions.

STABILITY: This product is stable under normal ambient conditions of temperature and pressure.

CONDITIONS TO AVOID: High temperatures, accumulation of static charges, flames, other possible ignition sources and moisture.

POSSIBILITY OF HAZARDOUS REACTIONS: None Known

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and carbon dioxide.

INCOMPATIBLE MATERIALS: Strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION**ACUTE TOXICITY**

Chemical Name	ORAL LD ₅₀	DERMAL LD ₅₀	INHALATION LC ₅₀
Titanium oxide (TiO ₂)	> 10000 mg/kg	> 10000 mg/kg	> 6.82 mg/l
1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich	> 10 g/kg	> 3.16 g/kg	> 0.13 mg/l
Carbon black	> 8000 g/kg	Not Established	Not Established
Aluminum Hydroxide	Not Established	Not Established	Not Established
Silica, Amorphous	Not Established	Not Established	Not Established

SKIN CORROSION/IRRITATION: No data available.

6835 GRAY**SERIOUS EYE DAMAGE/IRRITATION:** No data available.**RESPIRATORY OR SKIN SENSITISATION:** No data available.**GERM CELL MUTAGENICITY:** No data available.**CARCINOGENICITY**

Chemical Name	IARC Status
Titanium oxide (TiO ₂)	2B
Carbon black	2B
Silica, Amorphous	3

REPRODUCTIVE TOXICITY: No data available.**STOT-SINGLE EXPOSURE:** No data available.**STOT-REPEATED EXPOSURE:** No data available.**ASPIRATION HAZARD:** No data available.**12. ECOLOGICAL INFORMATION****ENVIRONMENTAL DATA:** No data available.**ECOTOXICOLOGICAL INFORMATION:** No specific ecological data are available for this product. Refer to Section 6 for information regarding accidental release and Section 15 for regulatory reporting information.**BIOACCUMULATION/ACCUMULATION:** No data available.**DISTRIBUTION:** No data available.**CHEMICAL FATE INFORMATION:** No data available.**13. DISPOSAL CONSIDERATIONS****DISPOSAL METHOD:** The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protections and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.**14. TRANSPORT INFORMATION****DOT (DEPARTMENT OF TRANSPORTATION):** Not Regulated**AIR (ICAO/IATA):** Not Regulated**VESSEL (IMO/IMDG):** Not Regulated**15. REGULATORY INFORMATION****UNITED STATES****SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)****311/312 HAZARD CATEGORIES:** None Expected**313 REPORTABLE INGREDIENTS:** This product does not contain any substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.**CERCLA (COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT)****CERCLA REGULATORY:** For this/these chemicals, release of more than the Reportable Quantity to the environment in a 24-hour period requires notification to the National Response Center (800-424-8802 or 202-426-2675):
None**TSCA (TOXIC SUBSTANCE CONTROL ACT)****TSCA REGULATORY:** This product does not contain any chemicals subject to TSCA Section 12(b) export notification.**TSCA STATUS:** This product or its components are listed in or exempt from the TSCA inventory requirements.**OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)**

6835 GRAY

29 CFR 1910.119---PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS CHEMICALS: None of the chemicals in this product are considered highly hazardous by OSHA.

CALIFORNIA PROPOSITION 65: This product contains chemical(s) which are known to the State of California to cause cancer, birth defects or other reproductive harm, and may be subject to the requirements of California Proposition 65 (CA Health & Safety Code Section 25249.5):

Chemical Name	Wt. %	Listed
1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich	15 - 40	Developmental Toxicity
Carbon black	5 - 10	Cancer

OSHA HAZARD COMM. RULE: The contents of the SDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

CANADA

WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM): This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

DOMESTIC SUBSTANCE LIST (INVENTORY): All components in this product are listed in or exempted from the Domestic Substances List (DSL) or the Non-Domestic Substances List (NDSL).

GENERAL COMMENTS:

DIDP RESTRICTIONS: This product contains diisodecyl phthalate (DIDP), CAS# 68515-49-1 EINECS# 271-091-4. In the U.S., there is an interim prohibition on DIDP above 0.1 percent by weight (one thousand parts per million) in toys intended for children age 12 and under that can be placed in a child's mouth and child care articles for children age 3 and under [H.R. 4040, The Consumer Safety Improvement Act of 2008]. In the EU, DIDP shall not be used as substance or as constituents of preparations, at concentrations of greater than 0.1 percent by weight (one thousand parts per million) of the plasticized material, in toys and child care articles which can be place in the mouth by children. Such toys and child care articles containing DIDP in concentrations greater than the limit mentioned above shall not be placed on the market [Directive 2005/84/EC].

16. OTHER INFORMATION


REASON FOR ISSUE: Revision

Date Revised: 06/17/2016

REVISION SUMMARY: This SDS replaces the 06/05/2013 SDS.

HMIS RATING

HEALTH	<input type="checkbox"/>	1
FLAMMABILITY	<input type="checkbox"/>	1
PHYSICAL HAZARD	<input type="checkbox"/>	0
PERSONAL PROTECTION	<input checked="" type="checkbox"/>	X

NFPA CODES

HMIS RATINGS NOTES: Personal Protection: See Section 8

MANUFACTURER DISCLAIMER: This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of BJB Enterprises, Inc. The data on this sheet relates only to the specific material designated herein. BJB Enterprises, Inc. assumes no legal responsibility for use or reliance upon this data.