

SAFETY DATA SHEET



Date Prepared : 04/07/2009
 SDS No : RELEASE #76
 Date Revised : 02/23/2016
 Revision No : 1

RELEASE #76

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: RELEASE #76
GENERAL USE: Release agent

MANUFACTURER

BJB Enterprises, Inc.
 14791 Franklin Avenue
 Tustin, CA 92780
Emergency Phone: (714) 734-8450

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (USA & Canada): (800) 424-9300
 or (703) 527-3887 CCN# 2820

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS**Health:**

Aspiration Hazard, Category 1
 Skin Irritation, Category 2
 Target Organ Toxicity (Single exposure), Category 3

Environmental:

Chronic Hazards to the Aquatic Environment, Category 2

Physical:

Flammable Liquids, Category 3

GHS LABEL

Flame



Health hazard

Exclamation
mark

Environment

SIGNAL WORD: DANGER

HAZARD STATEMENTS

H226: Flammable liquid and vapour.
 H304: May be fatal if swallowed and enters airways.
 H315: Causes skin irritation.
 H336: May cause drowsiness or dizziness.
 H411: Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS**Prevention:**

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P233: Keep container tightly closed.
 P240: Ground and bond container and receiving equipment.
 P241: Use explosion-proof [electrical/ventilating/lighting/...] equipment.
 P242: Use non-sparking tools.
 P243: Take action to prevent static discharges.
 P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

RELEASE #76

P271: Use only outdoors or in a well-ventilated area.

P264: Wash thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P273: Avoid release to the environment.

Response:

P370+P378: In case of fire: Use foam, dry chemical, or carbon dioxide for extinction.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician.

P331: Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P332+P313: If skin irritation occurs: Get medical advice/attention.

P363: Wash contaminated clothing before reuse.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312: Call a POISON CENTER/doctor/physician if you feel unwell.

P391: Collect spillage.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P235: Keep cool.

P405: Store locked up.

Disposal:

P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Naphtha (petroleum), heavy alkylate	60 - 100	64741-65-7

4. FIRST AID MEASURES

EYES: Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops.

SKIN: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if irritation or rash develops. Wash clothing before reuse.

INGESTION: Aspiration hazard. If swallowed, DO NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. Never give anything by mouth to an unconscious person. Get medical attention immediately.

INHALATION: Remove to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get immediate medical attention.

NOTES TO PHYSICIAN: Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

5. FIRE FIGHTING MEASURES

GENERAL HAZARD: Flammable liquid and vapor.

EXTINGUISHING MEDIA: Foam, dry chemical, or carbon dioxide.

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide, carbon dioxide, and various hydrocarbons.

EXPLOSION HAZARDS: Flammable liquid and vapor. Flashback along vapor trail may occur. This material may be ignited by heat, sparks, flame, or static electricity. Closed containers may explode when exposed to extreme heat. Heating can release vapor which can be ignited.

FIRE FIGHTING PROCEDURES: Cool fire exposed containers with water spray. Remove containers from the fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

FIRE FIGHTING EQUIPMENT: Firefighters should wear positive pressure self-contained breathing apparatus (SCBA) and consider use of unmanned hose holders or monitor nozzles for fighting large fires.

SENSITIVE TO STATIC DISCHARGE: This material can accumulate static charges which can cause an incendiary electrical discharge.

6. ACCIDENTAL RELEASE MEASURES

RELEASE #76

SMALL SPILL: Eliminate sources of ignition. Evacuate the area. Clean-up should only be performed by trained personnel. People dealing with a major spill should wear full protective clothing including appropriate respiratory protection. Prevent product spill from entering sewers or waterways. Neutralize small spills with a decontaminant.

LARGE SPILL: Contain and absorb large spills onto an inert, non-flammable adsorbent carrier (such as earth or sand). Do not use combustible materials such as saw dust. Use only spark resistant and explosion proof recovery devices. Shovel into open-top drums or plastic bags for further decontamination, if necessary. Wash the spill area clean with a liquid decontaminant. Remove and properly dispose of residues. Notify applicable government authorities if release is reportable. (See CERCLA in Section 15).

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Do not discharge into drains or rivers.

GENERAL PROCEDURES: Refer to section 8 of SDS for personal protection details.

RELEASE NOTES: Composition and extent of any spill should be evaluated against local regulations and reported to the proper agencies, if necessary.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Flammable liquid. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Avoid breathing vapor over open containers. Avoid open container exposure to damp air. Avoid breathing aerosols, mists, and vapors.

HANDLING: Use appropriate personal protective equipment as specified in Section 8. Handle in a well-ventilated area. Handle and use in a manner consistent with good industrial/manufacturing techniques and practices.

STORAGE: Store in a dry and well-ventilated place, away from excessive heat in the original or similar container. Avoid sources of ignition and incompatible materials. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials. Avoid unnecessary contact.

STORAGE TEMPERATURE: 65-80°F (18-27°C)

SHELF LIFE: 6 months from date of shipment under manufacturers recommended storage conditions.

ELECTROSTATIC ACCUMULATION HAZARD: This material can accumulate static charges which can cause an incendiary electrical discharge.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**EXPOSURE GUIDELINES**

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
Chemical Name	Type	EXPOSURE LIMITS		
		ppm	mg/m ³	
Naphtha (petroleum), heavy alkylate	OSHA PEL	TWA	NE	NE
		STEL	NE	NE
	ACGIH TLV	TWA	NE	NE
		STEL	NE	NE
	Supplier OEL	TWA	NE	NE
		STEL	NE	NE

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Safety goggles or glasses are recommended. Plastic face shields should be used for complete face protection to protect against possible splashing or spraying of material. ANSI Z87.1 or approved equivalent.

SKIN: Chemical-resistant gloves and chemical goggles, face-shield, and synthetic apron or coveralls should be used to prevent contact with eyes, skin, or clothing. Wear nitrile or neoprene gloves. Chemical resistant gloves lined with polyethylene offer maximum protection.

RESPIRATORY: Exhaust ventilation recommended. An organic vapor cartridge or fresh air supplied respirator (NIOSH approved) may be necessary for certain applications. Consider the type of application, environmental concentrations, and other materials being used concurrently when determining respirator use and selection. Observe OSHA regulations for respirator use (29 CFR 1910.134).

RELEASE #76

PROTECTIVE CLOTHING: Protective clothing should be selected and used in accordance with 'Guidelines for the Selection of Chemical Protective Clothing' published by ACGIH.

WORK HYGIENIC PRACTICES: Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Wash hands before eating.

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Training is important. Follow all label precautions.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Petroleum

COLOR: Colorless

pH: Not Applicable

PERCENT VOLATILE: 60-100

FLASH POINT AND METHOD: 48.9°C (120°F) Pinsky-Martens CC

FLAMMABLE LIMITS: 0.7% to 5%

AUTOIGNITION TEMPERATURE: 232.2°C (450°F)

VAPOR PRESSURE: Not Established

VAPOR DENSITY: > 1 (Air=1)

BOILING POINT: 171.1°C (340°F)

SOLUBILITY IN WATER: Not Established

SPECIFIC GRAVITY: 0.76 (water=1) at 25°C (77°F)

VISCOSITY: Not Established

(VOC): 456.000 to 760 g/l Calculated. Theoretical VOC minus water and exempt solvents.

10. STABILITY AND REACTIVITY

REACTIVITY: Hazardous reactions will not occur under normal transport or storage conditions.

STABILITY: This product is stable under normal ambient conditions of temperature and pressure.

CONDITIONS TO AVOID: Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces.

POSSIBILITY OF HAZARDOUS REACTIONS: No data available.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, and various hydrocarbons.

INCOMPATIBLE MATERIALS: Strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION**ACUTE TOXICITY**

Chemical Name	ORAL LD ₅₀	DERMAL LD ₅₀	INHALATION LC ₅₀
Naphtha (petroleum), heavy alkylate	> 2000 mg/kg	> 2000 mg/kg	> 10 mg/l (4 h)

SKIN CORROSION/IRRITATION: Causes skin irritation.

SERIOUS EYE DAMAGE/IRRITATION: No data available.

RESPIRATORY OR SKIN SENSITISATION: No data available.

GERM CELL MUTAGENICITY: No data available.

CARCINOGENICITY

NOTES: This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

REPRODUCTIVE TOXICITY: No data available.

STOT-SINGLE EXPOSURE: May cause drowsiness or dizziness.

STOT-REPEATED EXPOSURE: No data available.

ASPIRATION HAZARD: May be fatal if swallowed and enters airways.

RELEASE #76**12. ECOLOGICAL INFORMATION**

ENVIRONMENTAL DATA: This product may cause risk of hazardous effects to the environment.

ECOTOXICOLOGICAL INFORMATION: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Avoid release to the environment.

BIOACCUMULATION/ACCUMULATION: No data available.

DISTRIBUTION: No data available.

CHEMICAL FATE INFORMATION: No data available.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protections and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

EMPTY CONTAINER: Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. **DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.**

14. TRANSPORT INFORMATION**DOT (DEPARTMENT OF TRANSPORTATION)**

PROPER SHIPPING NAME: Petroleum distillates, n.o.s.

PRIMARY HAZARD CLASS/DIVISION: 3

UN/NA NUMBER: UN1268

PACKING GROUP: III

NAERG: 128

LABEL: Flammable liquid

AIR (ICAO/IATA)

SHIPPING NAME: Petroleum distillates, n.o.s.

UN/NA NUMBER: UN1268

PRIMARY HAZARD CLASS/DIVISION: 3

PACKING GROUP: III

ERG: 3L

LABEL: Flammable liquid

VESSEL (IMO/IMDG)

SHIPPING NAME: Petroleum distillates, n.o.s.

UN/NA NUMBER: UN1268

PRIMARY HAZARD CLASS/DIVISION: 3

PACKING GROUP: III

EmS: F-E, S-E

LABEL: Flammable liquid

15. REGULATORY INFORMATION**UNITED STATES****SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)**

311/312 HAZARD CATEGORIES: Acute health hazard. Fire hazard.

313 REPORTABLE INGREDIENTS: This product does not contain any substances subject to the reporting requirements of Section

RELEASE #76

313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

CERCLA (COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA REGULATORY: For this/these chemicals, release of more than the Reportable Quantity to the environment in a 24-hour period requires notification to the National Response Center (800-424-8802 or 202-426-2675):
None

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA REGULATORY: This product does not contain any chemicals subject to TSCA Section 12(b) export notification.

TSCA STATUS: This product or its components are listed in or exempt from the TSCA inventory requirements.

OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)

29 CFR1910.119---PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS CHEMICALS: None of the chemicals in this product are considered highly hazardous by OSHA.

CALIFORNIA PROPOSITION 65: This product does not contain any chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm, and may be subject to the requirements of California Proposition 65 (CA Health & Safety Code Section 25249.5).

OSHA HAZARD COMM. RULE: The contents of the SDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

CANADA

WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM): This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

DOMESTIC SUBSTANCE LIST (INVENTORY): All components in this product are listed in or exempted from the Domestic Substances List (DSL) or the Non-Domestic Substances List (NDSL).

GENERAL COMMENTS: No data available.

16. OTHER INFORMATION

REASON FOR ISSUE: Revision


Date Revised: 02/23/2016

REVISION SUMMARY: This SDS replaces the 04/07/2009 SDS.

HMIS RATING

HEALTH	1
FLAMMABILITY	2
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X

NFPA CODES



HMIS RATINGS NOTES: Personal Protection: See Section 8

MANUFACTURER DISCLAIMER: This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of BJB Enterprises, Inc. The data on this sheet relates only to the specific material designated herein. BJB Enterprises, Inc. assumes no legal responsibility for use or reliance upon this data.