

SAFETY DATA SHEET



Date Issued : 06/13/2011
 SDS No : TC-680 PART B
 Date Revised : 06/12/2018
 Revision No : 2

TC-680 PART B

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: TC-680 PART B
GENERAL USE: Polyurethane curative

MANUFACTURER

BJB Enterprises, Inc.
 14791 Franklin Avenue
 Tustin, CA 92780
Emergency Phone: (714) 734-8450

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (USA & Canada): (800) 424-9300
 or (703) 527-3887 CCN# 2820

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS**Health:**

Eye Irritation, Category 2A
 Skin Sensitization, Category 1
 Reproductive Toxicity, Category 1
 Target Organ Toxicity (Repeated exposure), Category 2

Environmental:

Acute Hazards to the Aquatic Environment, Category 1
 Chronic Hazards to the Aquatic Environment, Category 1

GHS LABEL

Health hazard

Exclamation
mark

Environment

SIGNAL WORD: DANGER**HAZARD STATEMENTS**

H319: Causes serious eye irritation.
 H317: May cause an allergic skin reaction.
 H360: May damage fertility or the unborn child.
 H373: May cause damage to organs through prolonged or repeated exposure.
 H410: Very toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS**Prevention:**

P201: Obtain special instructions before use.
 P202: Do not handle until all safety precautions have been read and understood.
 P260: Do not breathe dust/fume/gas/mist/vapours/spray.
 P264: Wash thoroughly after handling.
 P272: Contaminated work clothing should not be allowed out of the workplace.
 P280: Wear protective gloves/protective clothing/eye protection/face protection.
 P273: Avoid release to the environment.

Response:

TC-680 PART B

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P308+P313: IF exposed or concerned: Get medical advice/ attention.

P391: Collect spillage.

Storage:

P405: Store locked up.

Disposal:

P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Butyl benzyl phthalate (BBP)	60 - 100	85-68-7
Diethylmethylbenzenediamine	10 - 30	68479-98-1
2,6-di-tert-butyl-p-cresol	< 0.1	128-37-0
Benzene	< 0.0001	71-43-2

4. FIRST AID MEASURES

EYES: Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get immediate medical attention.

SKIN: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if irritation or rash develops. Wash clothing before reuse.

INGESTION: If swallowed, call a physician immediately. Do not induce vomiting unless directed to do so by medical personnel. Provided the patient is conscious, wash out mouth with water. Never give anything by mouth to an unconscious person.

INHALATION: Remove to fresh air. Seek medical attention if breathing becomes difficult or if respiratory irritation develops.

NOTES TO PHYSICIAN: Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Water spray, carbon dioxide, dry chemical, or foam.

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide, carbon dioxide, and nitrogen oxides.

FIRE FIGHTING PROCEDURES: Cool fire exposed containers with water spray. Remove containers from the fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

FIRE FIGHTING EQUIPMENT: Firefighters should wear positive pressure self-contained breathing apparatus (SCBA) and consider use of unmanned hose holders or monitor nozzles for fighting large fires.

6. ACCIDENTAL RELEASE MEASURES

SPILL AND LEAK PROCEDURES: Evacuate unnecessary personnel from the spill area. Eliminate all sources of ignition. Ensure adequate ventilation. Use personal protective equipment. Dike and contain spill. Prevent product from entering drains or waterways. Absorb with non-combustible material (such as sand, earth, diatomaceous earth, or vermiculite) and transfer to a container for disposal according to local/national regulations.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Do not discharge into drains, surface waters, or groundwater.

GENERAL PROCEDURES: Refer to section 8 of SDS for personal protection details.

RELEASE NOTES: Composition and extent of any spill should be evaluated against local regulations and reported to the proper agencies, if necessary.

TC-680 PART B

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Avoid breathing vapor over open containers. Avoid open container exposure to damp air. Avoid breathing aerosols, mists, and vapors.

HANDLING: Use appropriate personal protective equipment as specified in Section 8. Handle in a well-ventilated area. Handle and use in a manner consistent with good industrial/manufacturing techniques and practices.

STORAGE: Store in a dry and well-ventilated place, away from excessive heat, in original or similar container. Avoid unnecessary contact. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials.

STORAGE TEMPERATURE: 65-80°F (18-27°C)

SHELF LIFE: 6 months from date of shipment under manufacturers recommended storage conditions.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
Chemical Name	Type	EXPOSURE LIMITS		
			ppm	mg/m ³
Butyl benzyl phthalate (BBP)	OSHA PEL	TWA	-	-
		STEL	-	-
	ACGIH TLV	TWA	-	-
		STEL	-	-
	NIOSH REL	TWA	-	-
		STEL	-	-
Diethylmethylbenzenediamine	OSHA PEL	TWA	-	-
		STEL	-	-
	ACGIH TLV	TWA	-	-
		STEL	-	-
	NIOSH REL	TWA	-	-
		STEL	-	-
2,6-di-tert-butyl-p-cresol	OSHA PEL	TWA	-	-
		STEL	-	-
	ACGIH TLV	TWA	-	-
		STEL	-	-
	NIOSH REL	TWA	-	10
		STEL	-	-
Benzene	OSHA PEL	TWA	1	-
		STEL	5	-
	ACGIH TLV	TWA	0.5	-
		STEL	2.5	-
	NIOSH REL	TWA	0.1	0.319
		STEL	1	3.19

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

TC-680 PART B

EYES AND FACE: Safety goggles or glasses are recommended. Plastic face shields should be used for complete face protection to protect against possible splashing or spraying of material. ANSI Z87.1 or approved equivalent.

SKIN: Chemical-resistant gloves and chemical goggles, face-shield, and synthetic apron or coveralls should be used to prevent contact with eyes, skin, or clothing. Wear nitrile or neoprene gloves. Chemical resistant gloves lined with polyethylene offer maximum protection.

RESPIRATORY: Exhaust ventilation recommended. An organic vapor cartridge or fresh air supplied respirator (NIOSH approved) may be necessary for certain applications. Consider the type of application, environmental concentrations, and other materials being used concurrently when determining respirator use and selection. Observe OSHA regulations for respirator use (29 CFR 1910.134).

PROTECTIVE CLOTHING: Protective clothing should be selected and used in accordance with 'Guidelines for the Selection of Chemical Protective Clothing' published by ACGIH.

WORK HYGIENIC PRACTICES: Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Wash hands before eating.

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Training is important. Follow all label precautions.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Slight amine

COLOR: Amber

pH: No data available

PERCENT VOLATILE: 0.04

FLASH POINT AND METHOD: 157.2°C (315°F) Pensky-Martens CC

VAPOR PRESSURE: No data available

VAPOR DENSITY: No data available

BOILING POINT: No data available

SOLUBILITY IN WATER: Slightly soluble

SPECIFIC GRAVITY: 1.09 (water=1) at 25°C (77°F)

VISCOSITY #1: 60 Centipoise at 25°C (77°F)

(VOC): < 0.5 g/l Calculated. Theoretical VOC minus water and exempt solvents.

10. STABILITY AND REACTIVITY

REACTIVITY: Hazardous reactions will not occur under normal transport or storage conditions.

STABILITY: This product is stable under normal ambient conditions of temperature and pressure.

CONDITIONS TO AVOID: High temperatures, moisture, and freezing conditions.

POSSIBILITY OF HAZARDOUS REACTIONS: No data available

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, and nitrogen oxides.

INCOMPATIBLE MATERIALS: Isocyanates, strong oxidizing agents, and strong acids.

11. TOXICOLOGICAL INFORMATION**ACUTE TOXICITY**

Chemical Name	ORAL LD ₅₀	DERMAL LD ₅₀	INHALATION LC ₅₀
Butyl benzyl phthalate (BBP)	2330 mg/kg Rat	> 5000 mg/kg Rabbit	No data available
Diethylmethylbenzenediamine	> 500 mg/kg Rat	> 2000 mg/kg Rat	No data available
2,6-di-tert-butyl-p-cresol	No data available	No data available	No data available
Benzene	> 5960 mg/kg Rat	8263 mg/kg Rabbit	43.7 mg/l Rat (4 h)

SKIN CORROSION/IRRITATION: No data available

SERIOUS EYE DAMAGE/IRRITATION: Causes serious eye irritation.

TC-680 PART B**RESPIRATORY OR SKIN SENSITISATION:** No data available**GERM CELL MUTAGENICITY:** No data available**CARCINOGENICITY**

Chemical Name	NTP Status	IARC Status
Butyl benzyl phthalate (BBP)		3
2,6-di-tert-butyl-p-cresol		3
Benzene	1	1

REPRODUCTIVE TOXICITY: May damage fertility or the unborn child.**STOT-SINGLE EXPOSURE:** No data available**STOT-REPEATED EXPOSURE:** May cause damage to organs through prolonged or repeated exposure.**ASPIRATION HAZARD:** No data available**12. ECOLOGICAL INFORMATION****ENVIRONMENTAL DATA:** This product may cause risk of hazardous effects to the environment.**ECOTOXICOLOGICAL INFORMATION:** Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Avoid release to the environment.**BIOACCUMULATION/ACCUMULATION:** No data available**DISTRIBUTION:** No data available**CHEMICAL FATE INFORMATION:** No data available**13. DISPOSAL CONSIDERATIONS****DISPOSAL METHOD:** The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protections and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.**14. TRANSPORT INFORMATION****DOT (DEPARTMENT OF TRANSPORTATION)****PROPER SHIPPING NAME:** Environmentally hazardous substances, liquid, n.o.s. (**See Note**)**TECHNICAL NAME:** (butyl benzyl phthalate)**PRIMARY HAZARD CLASS/DIVISION:** 9**UN/NA NUMBER:** UN3082**PACKING GROUP:** III**NAERG:** 171**REPORTABLE QUANTITY (RQ) UNDER CERCLA:** 100 lbs. of butyl benzyl phthalate**LABEL:** Class 9 (miscellaneous hazardous materials)**MARINE POLLUTANT #1:** Yes**OTHER SHIPPING INFORMATION:** Applies ONLY to containers with a RQ of butyl benzyl phthalate (100 lbs.), otherwise not regulated.**AIR (ICAO/IATA)****SHIPPING NAME:** Environmentally hazardous substances, liquid, n.o.s. (**See Note**)**TECHNICAL NAME:** (butyl benzyl phthalate)**UN/NA NUMBER:** UN3082**PRIMARY HAZARD CLASS/DIVISION:** 9**PACKING GROUP:** III

TC-680 PART B**ERG:** 9L**LABEL:** Class 9 (miscellaneous hazardous materials)**NOTE:** Applies ONLY to containers with a RQ of butyl benzyl phthalate (100 lbs.), otherwise not regulated.**VESSEL (IMO/IMDG)****SHIPPING NAME:** Environmentally hazardous substance, liquid, n.o.s.**TECHNICAL NAME:** (butyl benzyl phthalate)**UN/NA NUMBER:** UN3082**PRIMARY HAZARD CLASS/DIVISION:** 9**PACKING GROUP:** III**EmS:** F-A,S-F**MARINE POLLUTANT #1:** Yes**LABEL:** Class 9 (miscellaneous hazardous materials)**15. REGULATORY INFORMATION****UNITED STATES****SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)****311/312 HAZARD CATEGORIES:** Acute Health Hazard, Chronic Health Hazard**313 REPORTABLE INGREDIENTS:** This product does not contain any substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.**CERCLA (COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT)****CERCLA REGULATORY:** This product contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical Name	Wt. %	CERCLA RQ
Butyl benzyl phthalate (BBP)	60 - 100	100 lbs.
Benzene	< 0.0001	10 lbs.

TSCA (TOXIC SUBSTANCE CONTROL ACT)**TSCA REGULATORY:** This product contains Diethylmethylbenzenediamine (CAS No: 68479-98-1) which is subject to TSCA 12(b), Section 4 export notification.**TSCA STATUS:** This product or its components are listed in or exempt from the TSCA inventory requirements.**OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)****29 CFR 1910.119---PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS CHEMICALS:** None of the chemicals in this product are considered highly hazardous by OSHA.**CALIFORNIA PROPOSITION 65: ⚠ WARNING:** This product can expose you to chemicals including [see table below], which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

Chemical Name	Wt. %	Listed
Butyl benzyl phthalate (BBP)	60 - 100	Developmental Toxicity
Benzene	< 0.0001	<ul style="list-style-type: none"> ● Cancer ● Developmental Toxicity ● Male Reproductive

OSHA HAZARD COMM. RULE: The contents of the SDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.**CANADA****WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM):** This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.**DOMESTIC SUBSTANCE LIST (INVENTORY):** All components in this product are listed in or exempted from the Domestic Substances List (DSL) or the Non-Domestic Substances List (NDSL).

TC-680 PART B**GENERAL COMMENTS:**

BBP RESTRICTIONS: This product contains butyl benzyl phthalate (BBP), CAS# 85-68-7 EINECS# 201-622-7. In the U.S., there is a Prohibition on the Sale of Certain Products Containing Phthalates. Children's toys or child care articles shall not contain above 0.1 percent by weight (one thousand parts per million) of BBP [H.R. 4040, The Consumer Safety Improvement Act of 2008]. In the EU, BBP shall not be used as substance or as constituents of preparations, at concentrations of greater than 0.1 percent by weight (one thousand parts per million) of the plasticized material, in toys and child care articles. Such toys and childcare articles containing BBP in concentrations greater than the limit mentioned above shall not be placed on the market [Directive 2005/84/EC].

16. OTHER INFORMATION


REASON FOR ISSUE: Revision

Date Revised: 06/12/2018

REVISION SUMMARY: This SDS replaces the 06/09/2015 SDS.

HMIS RATING

HEALTH	*	2
FLAMMABILITY		1
PHYSICAL HAZARD		0
PERSONAL PROTECTION	X	

NFPA CODES

HMIS RATINGS NOTES: Personal Protection: See Section 8

MANUFACTURER DISCLAIMER: This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of BJB Enterprises, Inc. The data on this sheet relates only to the specific material designated herein. BJB Enterprises, Inc. assumes no legal responsibility for use or reliance upon this data.