

SAFETY DATA SHEET



Date Prepared : 01/27/2012
 SDS No : WC-575 PART A
 Date Revised : 02/07/2018
 Revision No : 2

WC-575 PART A

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: WC-575 PART A
GENERAL USE: Polyurethane resin

MANUFACTURER

BJB Enterprises, Inc.
 14791 Franklin Avenue
 Tustin, CA 92780
Emergency Phone: (714) 734-8450

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (USA & Canada): (800) 424-9300
 or (703) 527-3887 CCN# 2820

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Acute Toxicity (Inhalation), Category 2
 Skin Irritation, Category 2
 Eye Irritation, Category 2A
 Respiratory Sensitization, Category 1
 Skin Sensitization, Category 1
 Germ Cell Mutagenicity, Category 1
 Carcinogenicity, Category 1
 Target Organ Toxicity (Single exposure), Category 3

GHS LABEL



Skull and
crossbones



Health hazard

SIGNAL WORD: DANGER

HAZARD STATEMENTS

H330: Fatal if inhaled.
 H315: Causes skin irritation.
 H319: Causes serious eye irritation.
 H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H317: May cause an allergic skin reaction.
 H340: May cause genetic defects.
 H350: May cause cancer.
 H335: May cause respiratory irritation.

PRECAUTIONARY STATEMENTS

Prevention:

P201: Obtain special instructions before use.
 P202: Do not handle until all safety precautions have been read and understood.
 P260: Do not breathe dust/fume/gas/mist/vapours/spray.
 P271: Use only outdoors or in a well-ventilated area.

WC-575 PART A

P284: In case of inadequate ventilation wear respiratory protection.

P264: Wash thoroughly after handling.

P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P310: Immediately call a POISON CENTER/doctor/physician.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

P308+P313: IF exposed or concerned: Get medical advice/ attention.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

Disposal:

P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Cycloaliphatic polymer	30 - 60	Proprietary
Dicyclohexylmethane-4,4'-diisocyanate	30 - 60	5124-30-1
Solvent naphtha (petroleum), light aromatic	0.5 - 1.5	64742-95-6
Xylene	0.1 - 1	1330-20-7
1,2,4-trimethylbenzene	0.1 - 1	95-63-6
Ethylbenzene	0.1 - 1	100-41-4
Cumene	< 0.02	98-82-8
N-Methylpyrrolidone	< 0.011	872-50-4
Toluene	< 0.01	108-88-3
Phenyl mercuric acetate	< 0.003	62-38-4

4. FIRST AID MEASURES

EYES: Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get immediate medical attention.

SKIN: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if irritation or rash develops. Wash clothing before reuse.

INGESTION: If swallowed, call a physician immediately. Do not induce vomiting unless directed to do so by medical personnel. Provided the patient is conscious, wash out mouth with water. Never give anything by mouth to an unconscious person.

INHALATION: Remove to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get immediate medical attention.

NOTES TO PHYSICIAN: Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Water spray, carbon dioxide, dry chemical, or foam.

WC-575 PART A

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide, carbon dioxide, nitrogen oxides, hydrogen cyanide, and isocyanate vapor.

FIRE FIGHTING PROCEDURES: Cool fire exposed containers with water spray. Remove containers from the fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

FIRE FIGHTING EQUIPMENT: Firefighters should wear positive pressure self-contained breathing apparatus (SCBA) and consider use of unmanned hose holders or monitor nozzles for fighting large fires.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Evacuate the area. Clean-up should only be performed by trained personnel. People dealing with a major spill should wear full protective clothing including appropriate respiratory protection. Prevent product spill from entering sewers or waterways. Neutralize small spills with a decontaminant.

LARGE SPILL: Contain and absorb large spills onto an inert, non-flammable adsorbent carrier (such as earth or sand). Shovel into open-top drums or plastic bags for further decontamination, if necessary. Wash the spill area clean with a liquid decontaminant. Remove and properly dispose of residues. Notify applicable government authorities if release is reportable. (See CERCLA in Section 15).

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Do not discharge into drains or rivers.

GENERAL PROCEDURES: Refer to section 8 of SDS for personal protection details.

RELEASE NOTES: Composition and extent of any spill should be evaluated against local regulations and reported to the proper agencies, if necessary.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Avoid breathing vapor over open containers. Avoid open container exposure to damp air. Avoid breathing aerosols, mists, and vapors.

HANDLING: Use appropriate personal protective equipment as specified in Section 8. Handle in a well-ventilated area. Handle and use in a manner consistent with good industrial/manufacturing techniques and practices.

STORAGE: Store in a dry and well-ventilated place, away from excessive heat, in original or similar container. Avoid unnecessary contact. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials.

STORAGE TEMPERATURE: 65-80°F (18-27°C)

SHELF LIFE: 6 months from date of shipment under manufacturers recommended storage conditions.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**EXPOSURE GUIDELINES**

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
Chemical Name	EXPOSURE LIMITS			
	Type		ppm	mg/m ³
Cycloaliphatic polymer	OSHA PEL	TWA	-	-
		STEL	-	-
	ACGIH TLV	TWA	-	-
		STEL	-	-
	NIOSH REL	TWA	-	-
		STEL	-	-
Dicyclohexylmethane-4,4'-diisocyanate	OSHA PEL	TWA	-	-
		STEL	-	-
		C	0.01 ^[1]	0.11 ^[1]
	ACGIH TLV	TWA	0.005	-
		STEL	-	-

WC-575 PART A

	NIOSH REL	TWA	-	-
		STEL	-	-
		C	0.01	0.11
Solvent naphtha (petroleum), light aromatic	OSHA PEL	TWA	-	-
		STEL	-	-
	ACGIH TLV	TWA	-	-
		STEL	-	-
	NIOSH REL	TWA	-	-
		STEL	-	-
Xylene	OSHA PEL	TWA	100	435
		STEL	-	-
	ACGIH TLV	TWA	100	-
		STEL	150	-
	NIOSH REL	TWA	100	435
		STEL	150	655
1,2,4-trimethylbenzene	OSHA PEL	TWA	-	-
		STEL	-	-
	ACGIH TLV	TWA	25	123
		STEL	-	-
	NIOSH REL	TWA	25	125
		STEL	-	-
Ethylbenzene	OSHA PEL	TWA	100	435
		STEL	-	-
	ACGIH TLV	TWA	100	-
		STEL	125	-
	NIOSH REL	TWA	100	435
		STEL	125	545
Cumene	OSHA PEL	TWA	50 ^[1]	245 ^[1]
		STEL	-	-
	ACGIH TLV	TWA	50	-
		STEL	-	-
	NIOSH REL	TWA	50 ^[1]	245 ^[1]
		STEL	-	-
N-Methylpyrrolidone	OSHA PEL	TWA	-	-
		STEL	-	-
	ACGIH TLV	TWA	-	-
		STEL	-	-

WC-575 PART A

Toluene	NIOSH REL	TWA	-	-
		STEL	-	-
	OSHA PEL	TWA	200	-
		STEL	-	-
		C	300	-
	ACGIH TLV	TWA	-	-
STEL		-	-	
NIOSH REL	TWA	100	375	
	STEL	150	560	
Phenyl mercuric acetate	OSHA PEL	TWA	-	-
		STEL	-	-
	ACGIH TLV	TWA	- ^[1]	0.1 as Hg ^[1]
		STEL	-	-
	NIOSH REL	TWA	-	0.05
		STEL	-	-
		C		0.1
	Footnotes:			
1. Skin				

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Safety goggles or glasses are recommended. Plastic face shields should be used for complete face protection to protect against possible splashing or spraying of material. ANSI Z87.1 or approved equivalent.

SKIN: Chemical-resistant gloves and chemical goggles, face-shield, and synthetic apron or coveralls should be used to prevent contact with eyes, skin, or clothing. Wear nitrile or neoprene gloves. Chemical resistant gloves lined with polyethylene offer maximum protection.

RESPIRATORY: Exhaust ventilation recommended. An organic vapor cartridge or fresh air supplied respirator (NIOSH approved) may be necessary for certain applications. Consider the type of application, environmental concentrations, and other materials being used concurrently when determining respirator use and selection. Observe OSHA regulations for respirator use (29 CFR 1910.134).

PROTECTIVE CLOTHING: Protective clothing should be selected and used in accordance with 'Guidelines for the Selection of Chemical Protective Clothing' published by ACGIH.

WORK HYGIENIC PRACTICES: Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Wash hands before eating.

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Training is important. Follow all label precautions.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Viscous liquid

ODOR: Slight

COLOR: Colorless

pH: No data available

PERCENT VOLATILE: 2.58

FLASH POINT AND METHOD: 98.9°C (210°F) Pensky-Martens CC

VAPOR PRESSURE: No data available

VAPOR DENSITY: No data available

WC-575 PART A**BOILING POINT:** No data available**SOLUBILITY IN WATER:** Insoluble, reacts slowly with water**SPECIFIC GRAVITY:** 1.07 (water=1) at 25°C (77°F)**VISCOSITY #1:** 4725 Centipoise at 25°C (77°F)**(VOC):** < 27.61 g/l Calculated. Theoretical VOC minus water and exempt solvents.**10. STABILITY AND REACTIVITY****REACTIVITY:** Hazardous reactions will not occur under normal transport or storage conditions.**STABILITY:** This product is stable under normal ambient conditions of temperature and pressure.**CONDITIONS TO AVOID:** High temperatures, moisture, and freezing conditions.**POSSIBILITY OF HAZARDOUS REACTIONS:** Reacts violently with amines (exothermic). Exothermic reactions with acids, alkalis, powerful oxidants, and alcohols. Reacts with water, whereby carbon dioxide is produced; pressure may build up in closed containers (danger of bursting).**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide, carbon dioxide, nitrogen oxides, hydrogen cyanide, and isocyanate vapor.**INCOMPATIBLE MATERIALS:** Water, strong bases, strong acids, strong oxidizing agents, alcohols, and amines.**11. TOXICOLOGICAL INFORMATION****ACUTE TOXICITY**

Chemical Name	ORAL LD ₅₀	DERMAL LD ₅₀	INHALATION LC ₅₀
Cycloaliphatic polymer	No data available	No data available	No data available
Dicyclohexylmethane-4,4'-diisocyanate	18200 mg/kg Rat	> 7000 mg/kg Rat	0.33 mg/l Rat (4 h, dust/mist)
Solvent naphtha (petroleum), light aromatic	> 3492 mg/kg Rat	> 3160 mg/kg Rabbit	> 6193 mg/m ³ Rat (4 h)
Xylene	3523 mg/kg Rat	12126 mg/kg Rabbit	5000 ppm Rat (4 h)
1,2,4-trimethylbenzene	> 3440 mg/kg Rat	No data available	18 mg/l Rat (4 h)
Ethylbenzene	3500 mg/kg Rat	15400 mg/kg Rabbit	4000 ppm Rat (4 h)
Cumene	2260 mg/kg Rat	No data available	No data available
N-Methylpyrrolidone	3914 mg/kg Rat	8000 mg/kg Rabbit	> 5100 ppm Rat (4 h)
Toluene	> 5580 mg/kg Rat	12196 mg/kg Rabbit	12500 to 28800 mg/m ³ Rat (4 h)
Phenyl mercuric acetate	41 mg/kg Rat	No data available	No data available

SKIN CORROSION/IRRITATION: Causes skin irritation.**SERIOUS EYE DAMAGE/IRRITATION:** Causes serious eye irritation.**RESPIRATORY OR SKIN SENSITISATION:** May cause sensitization by inhalation and skin contact.**GERM CELL MUTAGENICITY:** May cause genetic defects.**CARCINOGENICITY**

Chemical Name	IARC Status
Xylene	3
Ethylbenzene	2B
Cumene	2B
Toluene	3

REPRODUCTIVE TOXICITY: No data available**STOT-SINGLE EXPOSURE:** Inhalation - May cause respiratory irritation. - Respiratory system**STOT-REPEATED EXPOSURE:** No data available

WC-575 PART A**ASPIRATION HAZARD:** No data available**12. ECOLOGICAL INFORMATION****ENVIRONMENTAL DATA:** No data available**ECOTOXICOLOGICAL INFORMATION:** No specific ecological data are available for this product. Refer to Section 6 for information regarding accidental release and Section 15 for regulatory reporting information.**BIOACCUMULATION/ACCUMULATION:** No data available**DISTRIBUTION:** No data available**CHEMICAL FATE INFORMATION:** No data available**13. DISPOSAL CONSIDERATIONS****DISPOSAL METHOD:** The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protections and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.**14. TRANSPORT INFORMATION****DOT (DEPARTMENT OF TRANSPORTATION):** Not Regulated**AIR (ICAO/IATA):** Not Regulated**VESSEL (IMO/IMDG):** Not Regulated**15. REGULATORY INFORMATION****UNITED STATES****SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)****311/312 HAZARD CATEGORIES:** Acute Health Hazard, Chronic Health Hazard**313 REPORTABLE INGREDIENTS:** This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:**EPCRA SECTION 313 SUPPLIER NOTIFICATION**

Chemical Name	Wt. %	CAS	Comments
Dicyclohexylmethane-4,4'-diisocyanate	30 - 60	5124-30-1	Diisocyanate Compounds (Category Code N120)
Ethylbenzene	0.1 - 1	100-41-4	
Phenyl mercuric acetate	< 0.003	62-38-4	Mercury Compounds (Category Code N458)

CERCLA (COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT)**CERCLA REGULATORY:** For this/these chemicals, release of more than the Reportable Quantity to the environment in a 24-hour period requires notification to the National Response Center (800-424-8802 or 202-426-2675):

Chemical Name	Wt. %	CERCLA RQ
Xylene	0.1 - 1	100 lbs.
Ethylbenzene	0.1 - 1	1,000 lbs.
Cumene	< 0.02	5,000
Toluene	< 0.01	1,000 lbs.
Phenyl mercuric acetate	< 0.003	100 lbs.

TSCA (TOXIC SUBSTANCE CONTROL ACT)**TSCA STATUS:** This product or its components are listed in or exempt from the TSCA inventory requirements.**OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)**

WC-575 PART A

29 CFR1910.119---PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS CHEMICALS: None of the chemicals in this product are considered highly hazardous by OSHA.

CALIFORNIA PROPOSITION 65: This product contains chemical(s) which are known to the State of California to cause cancer, birth defects or other reproductive harm, and may be subject to the requirements of California Proposition 65 (CA Health & Safety Code Section 25249.5):

Chemical Name	Wt. %	Listed
Ethylbenzene	0.1 - 1	Cancer
Cumene	< 0.02	Cancer
N-Methylpyrrolidone	< 0.011	Developmental Toxicity
Toluene	< 0.01	Developmental Toxicity
Phenyl mercuric acetate	< 0.003	Developmental Toxicity

OSHA HAZARD COMM. RULE: The contents of the SDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

CANADA

WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM): This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

DOMESTIC SUBSTANCE LIST (INVENTORY): All components in this product are listed in or exempted from the Domestic Substances List (DSL) or the Non-Domestic Substances List (NDSL).

GENERAL COMMENTS: No data available

16. OTHER INFORMATION

REASON FOR ISSUE: Revision


Date Revised: 02/07/2018

REVISION SUMMARY: This SDS replaces the 02/06/2015 SDS.

HMIS RATING

HEALTH	*	3
FLAMMABILITY		1
PHYSICAL HAZARD		1
PERSONAL PROTECTION		X

NFPA CODES



HMIS RATINGS NOTES: Personal Protection: See Section 8

MANUFACTURER DISCLAIMER: This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of BJB Enterprises, Inc. The data on this sheet relates only to the specific material designated herein. BJB Enterprises, Inc. assumes no legal responsibility for use or reliance upon this data.