SAFETY DATA SHEET



Date Issued : 09/08/2009 **SDS No :** WC-792 PART A **Date Revised :** 06/22/2018

Revision No: 4

WC-792 PART A

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: WC-792 PART A **GENERAL USE:** Polyurethane resin

MANUFACTURER

BJB Enterprises, Inc. 14791 Franklin Avenue Tustin, CA 92780

Emergency Phone: (714) 734-8450

24 HR. EMERGENCY TELEPHONE NUMBERS CHEMTREC (USA & Canada): (800) 424-9300

or (703) 527-3887 CCN# 2820

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Acute Toxicity (Inhalation), Category 2 Skin Irritation, Category 2 Eye Irritation, Category 2A Respiratory Sensitization, Category 1 Skin Sensitization, Category 1 Target Organ Toxicity (Single exposure), Category 3

GHS LABEL



Skull and crossbones



Health hazard

SIGNAL WORD: DANGER

HAZARD STATEMENTS
H330: Fatal if inhaled.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317: May cause an allergic skin reaction.

H335: May cause respiratory irritation.

PRECAUTIONARY STATEMENTS

Prevention:

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P271: Use only outdoors or in a well-ventilated area.

P284: In case of inadequate ventilation wear respiratory protection.

P264: Wash thoroughly after handling.

P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P310: Immediately call a POISON CENTER/doctor/physician.

WC-792 PART A

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

Disposal:

P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Chemical Name | Wt.% | CAS |
|---|----------|------------|
| Dicyclohexylmethane-4,4'-diisocyanate | 60 - 100 | 5124-30-1 |
| Poly[oxy(methyl-1,2-ethanediyl)], .alphahydroomegahydroxy-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1), polymer with 1,1'-methylenebis[4-isocyanatocyclohexane] | 10 - 30 | 53170-03-9 |
| N-Methylpyrrolidone | < 0.04 | 872-50-4 |
| Phenyl mercuric acetate | < 0.01 | 62-38-4 |

4. FIRST AID MEASURES

EYES: Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get immediate medical attention.

SKIN: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if irritation or rash develops. Wash clothing before reuse.

INGESTION: If swallowed, call a physician immediately. Do not induce vomiting unless directed to do so by medical personnel. Provided the patient is conscious, wash out mouth with water. Never give anything by mouth to an unconscious person.

INHALATION: Remove to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get immediate medical attention.

NOTES TO PHYSICIAN: Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Water spray, carbon dioxide, dry chemical, or foam.

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide, carbon dioxide, and is ocyanate-containing vapors.

FIRE FIGHTING PROCEDURES: Cool fire exposed containers with water spray. Remove containers from the fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

FIRE FIGHTING EQUIPMENT: Firefighters should wear positive pressure self-contained breathing apparatus (SCBA) and consider use of unmanned hose holders or monitor nozzles for fighting large fires.

6. ACCIDENTAL RELEASE MEASURES

SPILL AND LEAK PROCEDURES: Evacuate unnecessary personnel from the spill area. Eliminate all sources of ignition. Ensure adequate ventilation. Use personal protective equipment. Dike and contain spill. Prevent product from entering drains or waterways. Absorb with non-combustible material (such as sand, earth, diatomaceous earth, or vermiculite) and transfer to a container for disposal according to local/national regulations.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Do not discharge into drains, surface waters, or groundwater.

GENERAL PROCEDURES: Refer to section 8 of SDS for personal protection details.

RELEASE NOTES: Composition and extent of any spill should be evaluated against local regulations and reported to the proper agencies, if

necessary.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Avoid breathing vapor over open containers. Avoid open container exposure to damp air. Avoid breathing aerosols, mists, and vapors.

HANDLING: Use appropriate personal protective equipment as specified in Section 8. Handle in a well-ventilated area. Handle and use in a manner consistent with good industrial/manufacturing techniques and practices.

STORAGE: Store in a dry and well-ventilated place, away from excessive heat, in original or similar container. Avoid unnecessary contact. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials.

STORAGE TEMPERATURE: 65-80°F (18-27°C)

SHELF LIFE: 6 months from date of shipment under manufacturers recommended storage conditions.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

| | EX | POSUR | E LIMIT | 'S |
|---|------------------------------|-------|----------|-----------------------------|
| Chemical Name | Туре | | ppm | mg/m³ |
| | OSHA PEL | TWA | - | - |
| | | STEL | - | - |
| | | С | 0.01 [1] | 011 [1] |
| St. 11. 1. d. 4.41.1" | ACGIH | TWA | 0.005 | - |
| Dicyclohexylmethane-4,4'-diisocyanate | TLV | STEL | - | - |
| | | TWA | - | - |
| | NIOSH REL | STEL | - | - |
| | | C | 0.01 | 0.11 |
| | OSHA | TWA | - | - |
| | PEL | STEL | - | - |
| Poly[oxy(methyl-1,2-ethanediyl)], .alphahydroomegahydroxy-, ether with 2-ethyl-2- | ACGIH | TWA | - | - |
| hydroxymethyl)-1,3-propanediol (3:1), polymer with 1,1'-methylenebis[4-isocyanatocyclohexane] | TLV | STEL | - | - |
| | NIOSH REL | TWA | - | - |
| | | STEL | - | - |
| | OSHA | TWA | - | - |
| | PEL | STEL | - | - |
| N-Methylpyrrolidone | ACGIH | TWA | - | - |
| Vinemyrpyrrondone | TLV | STEL | - | - |
| | NIOSH | TWA | - | - |
| | REL | STEL | - | - |
| | OSHA | TWA | - | - |
| | PEL | STEL | - | - |
| | ACGIH TLV NIOSH REL | TWA | _ [1] | 0.1 as Hg ^[1] |
| Phenyl mercuric acetate | | STEL | - | - |
| | | TWA | - | 0.05 |
| | | STEL | - | - |
| | | C | | 0.1 |

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Safety goggles or glasses are recommended. Plastic face shields should be used for complete face protection to protect against possible splashing or spraying of material. ANSI Z87.1 or approved equivalent.

SKIN: Chemical-resistant gloves and chemical goggles, face-shield, and synthetic apron or coveralls should be used to prevent contact with eyes, skin, or clothing. Wear nitrile or neoprene gloves. Chemical resistant gloves lined with polyethylene offer maximum protection.

WC-792 PART A

RESPIRATORY: Exhaust ventilation recommended. An organic vapor cartridge or fresh air supplied respirator (NIOSH approved) may be necessary for certain applications. Consider the type of application, environmental concentrations, and other materials being used concurrently when determining respirator use and selection. Observe OSHA regulations for respirator use (29 CFR 1910.134).

PROTECTIVE CLOTHING: Protective clothing should be selected and used in accordance with 'Guidelines for the Selection of Chemical Protective Clothing' published by ACGIH.

WORK HYGIENIC PRACTICES: Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Wash hands before eating.

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Training is important. Follow all label precautions.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Slight
COLOR: Colorless
pH: No data available

PERCENT VOLATILE: 0.04

FLASH POINT AND METHOD: 207.2°C (405°F) Pensky-Martens CC

VAPOR PRESSURE: No data available VAPOR DENSITY: No data available BOILING POINT: No data available

SOLUBILITY IN WATER: Reacts with water

SPECIFIC GRAVITY: 1.08 (water=1) at 25°C (77°F)

VISCOSITY #1: 650 Centipoise at 25°C (77°F)

(VOC): < 0.5 g/l Calculated. Theoretical VOC minus water and exempt solvents.

10. STABILITY AND REACTIVITY

REACTIVITY: Hazardous reactions will not occur under normal transport or storage conditions.

STABILITY: This product is stable under normal ambient conditions of temperature and pressure.

CONDITIONS TO AVOID: High temperatures, moisture, and freezing conditions.

POSSIBILITY OF HAZARDOUS REACTIONS: Reacts violently with amines (exothermic). Exothermic reactions with acids, alkalis, powerful oxidants, and alcohols. Reacts with water, whereby carbon dioxide is produced; pressure may build up in closed containers (danger of bursting).

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, and is ocyanate-containing vapors.

INCOMPATIBLE MATERIALS: Water, alcohols, amines, bases, acids, and strong oxidizers.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

WC-792 PART A

| Chemical Name | ORAL LD ₅₀ | DERMAL LD ₅₀ | INHALATION LC ₅₀ |
|---|--------------------------|----------------------------|-----------------------------------|
| Dicyclohexylmethane-4,4'-diisocyanate | 18200 mg/kg Rat | > 7000 mg/kg Rat | 0.33 mg/l Rat (4 h, dust/mist) |
| Poly[oxy(methyl-1,2-ethanediyl)], .alphahydroomegahydroxy-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1), polymer with 1,1'-methylenebis[4-isocyanatocyclohexane] | No data available | No data available | No data available |
| N-Methylpyrrolidone | 3914 mg/kg Rat | 8000 mg/kg Rabbit | > 5100 ppm Rat (4 h) |
| Phenyl mercuric acetate | 41 mg/kg Rat | No data available | No data available |

SKIN CORROSION/IRRITATION: Causes skin irritation.

SERIOUS EYE DAMAGE/IRRITATION: Causes serious eye irritation.

RESPIRATORY OR SKIN SENSITISATION: May cause sensitization by inhalation and skin contact.

GERM CELL MUTAGENICITY: No data available

CARCINOGENICITY

NOTES: This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

REPRODUCTIVE TOXICITY: No data available

STOT-SINGLE EXPOSURE: Inhalation - May cause respiratory irritation. - Respiratory system

STOT-REPEATED EXPOSURE: No data available

ASPIRATION HAZARD: No data available

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: No data available

ECOTOXICOLOGICAL INFORMATION: No specific ecological data are available for this product. Refer to Section 6 for information regarding accidental release and Section 15 for regulatory reporting information.

BIOACCUMULATION/ACCUMULATION: No data available

DISTRIBUTION: No data available

CHEMICAL FATE INFORMATION: No data available

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protections and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION): Not Regulated

AIR (ICAO/IATA): Not Regulated VESSEL (IMO/IMDG): Not Regulated

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Acute Health Hazard, Chronic Health Hazard

313 REPORTABLE INGREDIENTS: This product contains the following substances subject to the reporting requirements of Section

313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

EPCRA SECTION 313 SUPPLIER NOTIFICATION

| Chemical Name | Wt.% | CAS | Comments |
|---------------------------------------|----------|-----------|---|
| Dicyclohexylmethane-4,4'-diisocyanate | 60 - 100 | 5124-30-1 | Diisocyanate Compounds (Category Code N120) |
| Phenyl mercuric acetate | < 0.01 | 62-38-4 | Mercury Compounds (Category Code N458) |

CERCLA (COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA REGULATORY: This product contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

| Chemical Name | Wt.% | CERCLA RQ |
|-------------------------|--------|-----------|
| Phenyl mercuric acetate | < 0.01 | 100 lbs. |

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA REGULATORY: This product does not contain any substances subject to TSCA Section 12(b) export notification.

TSCA STATUS: This product or its components are listed in or exempt from the TSCA inventory requirements.

OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)

29 CFR1910.119---PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS CHEMICALS: None of the chemicals in this product are considered highly hazardous by OSHA.

CALIFORNIA PROPOSITION 65: ▲ **WARNING:** This product can expose you to chemicals including [see table below], which are known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

| Chemical Name | Wt.% | Listed |
|-------------------------|--------|------------------------|
| N-Methylpyrrolidone | < 0.04 | Developmental Toxicity |
| Phenyl mercuric acetate | < 0.01 | Developmental Toxicity |

OSHA HAZARD COMM. RULE: The contents of the SDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

CANADA

WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM): This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

DOMESTIC SUBSTANCE LIST (INVENTORY): All components in this product are listed in or exempted from the Domestic Substances List (DSL) or the Non-Domestic Substances List (NDSL).

GENERAL COMMENTS: No data available


16. OTHER INFORMATION

REASON FOR ISSUE: Revision

Date Revised: 06/22/2018

REVISION SUMMARY: This SDS replaces the 06/23/2015 SDS.





HMIS RATINGS NOTES: Personal Protection: See Section 8

MANUFACTURER DISCLAIMER: This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of BJB Enterprises, Inc. The data on this sheet relates only to the specific material designated herein. BJB Enterprises, Inc. assumes no legal responsibility for use or reliance upon this data.